

Switching device combination - SOL-SC-2ST-0-DC-2MPPT-1001SE - 1016813

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



String combiner box for photovoltaic systems up to 1000 V DC for the connection of 2x 2 strings. With surge protection and SUNCLIX DC connector for the input and output side.

Product Description

The Solarline string combiner boxes (SCBs) are used in both small rooftop systems and large ground-mounted systems. Their functions include collecting and protecting strings and, if necessary, separating the panels from the rest of the system by means of a fire service or switch disconnectors.

Your advantages

- ✓ Fast installation and startup
- ✓ Large portfolio of string combiner boxes in stock
- ✓ Application-oriented consultation
- ✓ Standard-compliant switchgear and controlgear assembly, thanks to use of DIN EN 61439

RoHS

Key Commercial Data

Packing unit	1 pc
GTIN	 4 055626 498355
GTIN	4055626498355
Weight per Piece (excluding packing)	2,750.000 g
Weight per piece (including packing)	2,750.000 g
Custom tariff number	85363030
Country of origin	Germany
Sales Key	V1 - Terminl Blocks+Boxes

Technical data

System parameter

System voltage	1000 V DC (U_{max})
Number of string inputs	2 (per MPP tracker)
Number of outputs	1 (per MPP tracker)

Switching device combination - SOL-SC-2ST-0-DC-2MPPT-1001SE - 1016813

Technical data

System parameter

Number of supported MPP trackers	2
----------------------------------	---

Safety equipment

Surge protective device	T1 / T2
Protection level U_p	≤ 3.5 kV
Total discharge current I_{total} (8/20) μ s	40 kA
Total discharge current I_{total} (10/350) μ s	5 kA

Cable entry

Type of cable entry	SUNCLIX
Cable cross section string input	2.5 mm ² ... 6 mm ²
Cable cross section output	2.5 mm ² ... 6 mm ²
Cable cross section grounding	16 mm ² (2 x)
Sealing area grounding	6 mm ... 12 mm

General data

Housing material	Polycarbonate
Material cover/door	Polycarbonate (transparent)
Degree of protection	IP65
Protection class	II

Dimensions

Outer dimensions: width, height, depth	254 mm x 180 mm x 111 mm (Housing dimensions)
--	---

Ambient conditions

Ambient temperature (operation)	-20 °C ... 55 °C
---------------------------------	------------------

Drawings

Schematic diagram



Connection of the protective grounding conductor


Schematic diagram




Connection of the protective equipotential bonding conductor

Switching device combination - SOL-SC-2ST-0-DC-2MPPT-1001SE - 1016813

Connection diagram




Dimensional drawing



Housing dimensions


Schematic application drawing

Schematic diagram




Connection of the PV strings

Schematic diagram



Connection to the inverter

Circuit diagram



Connection of the remote indication contact on the surge protection

Classifications

eCl@ss

eCl@ss 5.1	27371890
eCl@ss 8.0	27142422
eCl@ss 9.0	27142422

Switching device combination - SOL-SC-2ST-0- DC-2MPPT-1001SE - 1016813

Classifications

ETIM

ETIM 4.0	EC000816
ETIM 5.0	EC000268
ETIM 6.0	EC000268

Accessories

Accessories

Photovoltaic connector

Connector - PV-CF-S 2,5-6 (+) - 1774674



Photovoltaic connector, Connector, : 0 mm, color: black, number of positions: 1, Min. wire cross section: 2.5, Max. conductor cross section: 6, Rated current: 27 A, Connection method: Spring-cage connection, Type of contact: Socket. can only be released using a tool

Connector - PV-CM-S 2,5-6 (-) - 1774687



Photovoltaic connector, Connector, : 0 mm, color: black, number of positions: 1, Min. wire cross section: 2.5, Max. conductor cross section: 6, Rated current: 27 A, Connection method: Spring-cage connection, Type of contact: Pin. can only be released using a tool

Connector - PV-CF-S 6-16 (+) - 1790784



Photovoltaic connector, Connector, color: black, number of positions: 0, Min. wire cross section: 6, Max. conductor cross section: 16, Rated current: 40 A, Connection method: Spring-cage, Type of contact: Socket. can only be released using a tool

Connector - PV-CM-S 6-16 (-) - 1790797



Photovoltaic connector, Connector, color: black, number of positions: 0, Min. wire cross section: 6, Max. conductor cross section: 16, Rated current: 40 A, Connection method: Spring-cage, Type of contact: Pin. can only be released using a tool

Switching device combination - SOL-SC-2ST-0-DC-2MPPT-1001SE - 1016813

Accessories

Photovoltaic Y-distributor - PV-ED6/Y-120(2+/1-) - 1030649

Photovoltaic Y distributor, nominal current: 35 A, color: black. Assembled with SUNCLIX - 1x male (minus) - 2x female (plus); length of single cable 0.12 m, varying number of nodes and customer-specific cable lengths are available on request.



Photovoltaic Y-distributor - PV-ED6/Y-120(1+/2-) - 1030650

Photovoltaic Y distributor, nominal current: 35 A, color: black. Assembled with SUNCLIX - 1x female (plus) - 2x male (minus); length of single cable 0.12 m, varying number of nodes and customer-specific cable lengths are available on request.



Protective cap

Protective cap - PV-C PROTECTION CAP - 1785430

Protective cap for SUNCLIX photovoltaic connector; transport protection for the mating face.



Replacement plug

Type 1/2 surge protection plug - VAL-MS-T1/T2 1000DC-PV-ST - 2801162



Replacement plug for PV arrester combinations from the VAL-MS-T1/T2 1000DC-PV-... product range

Photovoltaic adapter set - PV-AS-MC4/6-150-MN-SET1 - 1079531



The SUNCLIX adapter set enables SUNCLIX connectors to be connected to type MC4 connectors from Multi Contact without voiding the product warranty or guarantee for the MC4 connectors.

