

# 400V Junction Cabinet

---



## Product Advantages

- Non-Walk-In design with less footprint
- Easy installation and O&M
- Support installation against wall
- Maximum 6 Energy Storage Cabinets in Parallel



| Model                         |                                     | PAC-750K-H1    |
|-------------------------------|-------------------------------------|----------------|
| Input side                    |                                     |                |
| Rated operating voltage       | 400V AC, Three-phase four-wire      |                |
| Rated current                 | 6*180A (max 6 cabinets in parallel) |                |
| Maximum current               | Max 1188A                           |                |
| Rated input power             | 6*125kW                             |                |
| System Parameters             |                                     |                |
| Operating ambient temperature | -30℃~50℃ (Derating above 45℃)       |                |
| Storage ambient temperature   | -30℃~60℃                            |                |
| Relative humidity             | 0~100% (No condensation)            |                |
| Maximum operating altitude    | ≤2000m (Customized if above)        |                |
| Ingress protection rating     | IP55                                |                |
| Anti-corrosion                | C4 (C5 optional)                    |                |
| Wire inlet & outlet           | Bottom inlet, bottom outlet         |                |
| Dimension(W*D*H)              | 700*700*2182mm                      |                |
| Weight                        | < 300kg                             |                |
| Installation                  | Ground mounting                     |                |
| Standard                      |                                     | IEC/EN 61439-2 |

\* All specifications are subject to change without notice.