


OASIS L344

344kWh Liquid Cooled Battery Cabinet



Application Scenario



PV and Storage Integration

OASIS L344 supports external hybrid inverter, DC coupling access to photovoltaic, integrated system design, one-stop service, high system integration, flexible layout of the scheme, can reduce light abandonment, improve the utilization rate of photovoltaic power generation.



Peak shaving and valley filling

After the OASIS L344 external energy storage inverter is connected, the user charges the energy storage system when the price is low, and takes electricity directly from the energy storage battery without purchasing electricity from the grid during the peak time, thereby avoiding the peak price and reducing the electricity cost.



Emergency Backup

OASIS L344 external hybrid inverter is also suitable for applications that require high continuity of the power grid. When the power grid is cut off, it can be used as a backup power supply to replace the traditional UPS power supply function, and provide backup power supply protection for the critical uninterruptible load in the industrial and commercial park to cope with sudden power failure.



Micro-grid

OASIS L344 can form a microgrid system with inverters, photovoltaic arrays, loads, diesel generators, etc. which is widely used in remote mountain areas, areas without electricity, islands, communication base stations and other places.



Cloud Platform Scheduling

OASIS L344 supports external intelligent EMS system, real-time status monitoring and fault recording, fault warning and fault location; Supports external cloud platform functions to achieve remote scheduling, cluster control, and energy efficiency management, enabling global assets to be visualized and digitized, and improving management efficiency.



Frequency and Peak Modulation

OASIS L344 can support 1C fast discharge after connecting to the grid-connected inverter, provide load support during the peak of power consumption, and participate in the load balance of the grid. At the same time, when the power grid frequency fluctuations, as a response to provide fast frequency modulation scheduling services.




OASIS L344

Single Cluster Solution	
Model Type	OASIS L344
Rated energy	344kWh
Cell Specification	3.2V 280Ah
PACK Capacity	43.008kWh
No.of modules	8
Rated voltage	1228.8V
Voltage range	998.4~1401.6V
Max. C-rate	1C
Ambient temperature	-30℃~55℃
Working relative humidity	0~95% (no condensation)
Altitude	2000m
Cooling method	Liquid cooling
Fire suppression system	Cluster level aerosol agent fire suppression+combustible gas detection and ventilation linkage+deflagration relief panel
Auxiliary power supply	220VAC/50Hz; 110VAC/60Hz; 110VAC/60Hz
Communication interface	CAN/RS485/Ethernet
Enclosure protection rating	IP55
Dimensions(W*D*H)	1570mm*1350mm*2380mm
Weight	3480kg
Accreditation	CE/IEC62619/UL1973/UN38.3/IEC62477

Approved Compatibility List of Inverter Brands

Inverter brand	Inverter model	SUNWODA ENERGY BATTERY SERIES
		OASIS L344
KACO	K A C O	92.0 TL3-S/110 TL3-S/137 TL3-S

Case Sharing




Germany
OASIS L344 & Kaco
184kW/688kWh
Outdoor Battery Storage System
BESS for Self-consumption




SUNWODA
ENERGY

OASIS
L344



OASIS L344

| 344kWh Liquid Cooled Battery Cabinet



Highlights

0.2C~1C

The inverter with different power can be selected, and the maximum support is 1C

9000 cycles

SUNWODA self-developed long life Cells are selected

100%DOD

Discharge depth up to 100%, maximize economy

kWh-MWh+

Supports parallel capacity expansion

< 2.2m²

A single cabinet covers an area of less than 2.2m²

C4/IP65

C4 anti-corrosion grade, Pack-level IP65, cabinet IP55, strong environmental adaptability



www.sunwodaenergy.com

SUNWODA ENERGY TECHNOLOGY CO., LTD.

Address: 15th Floor, Building B, Sunwoda Industrial Park, No. 18 Tangjianshan Road, Guangming District, Shenzhen, China
E-mail: info@sunwoda.com Tel: +86 755 2267 0380