

# Smart Energy Hot Water For Australia

SMRT-HOT-WTR-48-S1



SMART ENERGY

## Maximises self-consumption by storing excess solar energy as hot water

- Seamless integration with all SolarEdge inverters, and the monitoring platform
- Adjusts power supplied to the heater based on available PV power (up to 4.8 kW)
- Built-in water tank power-consumption meter
- Simple wall mount installation with an IP65 protection rating
- Wireless communication with the inverter
- Suitable for powering purely resistive loads only
- Optional temperature sensor for optimised heating

# Smart Energy Hot Water For Australia

## SMRT-HOT-WTR-48-S1

SMRT-HOT-WTR-48-S1		UNIT
<b>ELECTRICAL SERVICE</b>		
Operating Voltage Range	207-264	Vac
AC Frequency	50	Hz
Nominal Voltage	230	Vac
Supported Grids	L / N / PE	
Maximum Supported Load Size	4.8	kW
Maximum Load Current Rating	21	A
Input Over voltage protection <sup>(1)</sup>	264	Vac
Minimum Output Power	5% of load rating	
Load Type	Resistive	
Efficiency	> 98	%
Output Over-current Protection	22	A
External Over-current Protective Device Rating	≥ 25	A
Type of Action	Type 1 C	
Over Voltage Category <sup>(2)</sup>	III	
<b>COMMUNICATION</b>		
Supported Communication Protocol	ZigBee Home Automation	
Device Configuration	Via SetApp, the inverter LCD or the monitoring platform / app	
Nominal Transmit Power	11.8	dBm
Operating Frequency Range	2.4 - 2.5	GHz
Bandwidth	2	MHz
Modulation	O-QPSK with DSSS coding	
Outdoor (LOS) Range	400 / 1312	m / ft
Indoor Range <sup>(3)</sup>	50 / 164	m / ft
EIRP with Antenna	16.8	dBm
Maximum Emitted Power	≤ 20	dBm
<b>STANDARD COMPLIANCE</b>		
Radio	ETSI EN 300 328 V 1.8.1, ETSI EN 301 489-1, ETSI EN 301 489-17	
Safety	IEC-60730 -1	
EMC	EN61000-6-1 2 3, EN61000-4-2 3 4 5 6 8 11	
<b>INSTALLATION SPECIFICATIONS</b>		
Dimensions (H x W x D)	375 x 240 x 110 / 14.7 x 9.5 x 4.5	mm / inch
Weight	5.3 / 11.7	kg / lb
Operating Temperature Range	-10 to +50 / 14 to 122	°C / °F
Maximum distance between Device and Load/Cable cross section	3/10 for 13 AWG/2.5 mm <sup>2</sup> 20/65 for 11 AWG/4 mm <sup>2</sup>	m / ft
Terminal Block Minimum Wire Cross Section	1.5 / 15	mm <sup>2</sup> / AWG
Interfaces	1. AC in 2. AC out 3. External antenna, RP-SMA	
Conduits	Pre-drilled openings of 25 mm for 2 conduits	
Mounting Type	Wall mount	
Pollution Degree	3	
IP Rating	IP65	
<b>SENSOR SPECIFICATIONS<sup>(4)</sup></b>		
Sensor type	Pt100 (100 Ohms @ 0°C) to IEC 751, Class B, 3/4 wire	
Construction	6.0mm diameter stem in 316 stainless steel	
Termination	IP67 aluminium alloy weatherproof connection head with 4 wire connection block, M20 x 1.5mm cable entry (gland included)	
Process connection	1/2" BSP parallel	
Probe temperature range	-100°C to +450°C (connection head @ 170°C)	
Probe Diameter	Ø6mm (1/4")	
Probe length	150mm 1/2" BSPP	


<sup>(1)</sup> The device stops diverting power to the load when this threshold is exceeded

<sup>(2)</sup> Working voltage of 300 Vac

<sup>(3)</sup> Approximate values. May differ depending on specific installation conditions

<sup>(4)</sup> Temperature sensor ordered separately. For more information please contact SolarEdge

# / SolarEdge System with Smart Energy Hot Water For Australia



## Temperature Sensor<sup>(4)</sup>

