

Characteristics of a PV module

Manufacturer, model : **Trina Solar, TSM-550DEG19C.20**

Availability : Prod. Since 2020

Data source : TSL_2020_7

STC power (manufacturer)	Pnom	550 Wp	Technology		Si-mono
Module size (W x L)	1.096 x 2.384	m ²	Rough module area	Amodule	2.61 m ²
Number of cells	2 x 55		Sensitive area (cells)	Acells	2.43 m ²

Specifications for the model (manufacturer or measurement data)

Reference temperature	TRef	25 °C	Reference irradiance	GRef	1000 W/m ²
Open circuit voltage	Voc	38.1 V	Short-circuit current	Isc	18.39 A
Max. power point voltage	Vmpp	31.8 V	Max. power point current	Impp	17.29 A
=> maximum power	Pmpp	549.8 W	Isc temperature coefficient	mulsc	7.3 mA/°C

One-diode model parameters

Shunt resistance	Rshunt	800 ohm	Diode saturation current	IoRef	0.026 nA
Serie resistance	Rserie	0.13 ohm	Voc temp. coefficient	MuVoc	-104 mV/°C
Specified Pmax temper. coeff.	muPMaxR	-0.34 %/°C	Diode quality factor	Gamma	0.99
			Diode factor temper. coeff.	muGamma	0.000 1/°C

Reverse Bias Parameters, for use in behaviour of PV arrays under partial shadings or mismatch

Reverse characteristics (dark)	BRev	3.20 mA/V ²	(quadratic factor (per cell))	
Number of by-pass diodes per module		3	Direct voltage of by-pass diodes	-0.7 V

Model results for standard conditions (STC: T=25° C, G=1000 W/m², AM=1.5)

Max. power point voltage	Vmpp	31.4 V	Max. power point current	Impp	17.59 A
Maximum power	Pmpp	551.8 Wc	Power temper. coefficient	muPmpp	-0.34 %/°C
Efficiency(/ Module area)	Eff_mod	21.1 %	Fill factor	FF	0.787
Efficiency(/ Cells area)	Eff_cells	22.7 %			

