

SH3/3.6/4RL
SBL060

NEW



SUPERIOR EFFICIENCY

Maximize Energy, Minimize Waste

- 20 A Input for Mainstream PV Panels
- Wide MPPT Range (40 V Min.)
- Patented PID Zero



EVEN MORE DURABLE

Power Your House for Longer!

- 314 Ah Cells with Battery Optimizer for Long Service Life
- IP65 Waterproof & C5-M Corrosion-Resistant



UPGRADED SAFETY

Shield Your Home from Every Risk

- Patented Explosion-Proof Design
- Real-Time Battery Monitoring with Active Protection Kit
- AFCI Protection



ALWAYS POWERFUL

Master Energy In and Out, Anytime

- Full Power Backup at 45 °C , Good Operation at -20 °C
- Up to 2 Inverters & Each Inverter Support 4 Battery Packs Parallel
- Peak backup output up to 200%, 10 s



NEXT LEVEL BACKUP

System Flexibility in Every Scenario

- 4 ms Seamless Switch¹⁾
- Diesel Generator, Micro inverter & EV charger Compatibility²⁾
- Retrofit or New Installation for Whole-Home Backup



INTELLIGENT ENERGY MANAGEMENT

Control Energy at Your Fingertips

- iHomeManager (iHM) with Smart Load³⁾
- iSolarCloud App
- Intelligent IV Scanning & Fault Recording
- Battery Integrated BMS (battery management system)



Type designation	SH3RL	SH3.6RL	SH4RL
Input (DC)			
Recommended max. PV input power	6000 Wp	7200 Wp	8000 Wp
Max. usable PV input power	4800 Wp	5670 Wp	6400 Wp
Max. PV input voltage		500 V	
Min. PV input voltage / Startup input voltage		40 V / 50 V	
Rated PV input voltage		360 V	
MPPT operating voltage range ⁴⁾		40 V - 425 V	
No. of independent MPP trackers		2	
No. of PV strings per MPPT		1 / 1	
Max. PV input current		40 A (20 A / 20 A)	
Max. DC short-circuit current		50 A (25 A / 25 A)	
Max. current for input connector		25 A	
Battery data			
Battery type		Li-ion battery	
Battery voltage range		40 V – 60 V	
Max. charge / discharge current ⁵⁾	120 A / 75 A	120 A / 90 A	120 A / 100 A
Max. charge / discharge power	5000 W / 3000 W	5000 W / 3600 W	5000 W / 4000 W
Input / Output (AC)			
Max. AC power from grid		8800 W	
Rated AC output power	3000 W	3680 W	4000 W
Max. AC output apparent power	3000 VA	3680 VA	4000 VA
Max. AC output current	13.6 A	16 A	18.2 A
Rated AC voltage		220 V / 230 V / 240 V	
AC voltage range		154 V – 276 V	
Rated grid frequency		50 Hz / 60 Hz	
Grid frequency range		45 Hz – 55 Hz / 55 Hz – 65 Hz	
Harmonic (THD)		< 3% (of rated power)	
Power factor at rated power / Adjustable power factor	> 0.99 at default value at rated power / 0.8 leading to 0.8 lagging		
Feed-in phases / Connection phases		1 / 1	
Backup data (on grid mode)			
Max. output power for backup load ⁶⁾		8800 W	
Max. output current for backup load		40 A	
Backup data (off-grid mode)			
Rated voltage		220 V / 230 V / 240 V	
Rated frequency		50 Hz / 60 Hz	
THDV (@ Linear load)		< 2%	
Backup switch time		≤ 4 ms	
Rated output power	3000 W	3680 W	4000 W
Max. output power for backup load	3300 W	4048 W	4400 W
Peak output power		2 times of rated power, 10 s	
Efficiency			
Max. efficiency / European efficiency		97.2% / 96.2%	
Protection & Function			
Grid monitoring		Yes	
DC reverse polarity protection		Yes	
AC short-circuit protection		Yes	
Leakage current protection		Yes	
DC switch (solar)		Yes	
Surge protection		DC Type II / AC Type II	
PID Zero		Yes	
Arc fault circuit interrupter (AFCI)		Yes	
Micro-inverter compatibility ⁷⁾		Optional	
General data			
Topology (Inverter)		Non-isolated	
Topology (Battery BDC)		Isolated	
Degree of protection		IP65	
Dimensions (W * H * D)		532 mm * 386 mm * 210 mm	
Weight		< 19 kg	
Mounting method		Wall-mounting bracket	
Operating ambient temperature range		-25 °C to 60 °C	
Allowable relative humidity range		0% – 95%	
Cooling method		Natural convection	
Max. operating altitude		3000 m	
Noise (typical)		≤ 35 dB (A)	
Display		LED	
Communication		CAN, RS485, Ethernet, WLAN	
DI / DO		DI *1 / DO *1	
DC connection type		MC4 (Max.6 mm²)	
Battery connection type		OT terminal (35 mm² mm²)	
AC connection type		Plug and Play (Max. 8 AWG)	
Grid compliance	IEC 62109-1/-2, IEC/EN 61000-6-1/-3, IEC 63027, IEC 62116, IEC 61727, EN 50549, VDE-AR-N 4105, G98, G99, UNE, NTS, CEI 0-21		

Type designation		SBL060
System data		
Battery type		LiFePO4
Nominal energy		6.0 kWh
Usable energy		5.8 kWh
Nominal voltage		51.2 V
Recommended charging/discharging power		3.0 kW / 2.9 kW
Peak charging/discharging power ⁸⁾		3.75 kW / 3.7 kW
Communication		
Display		LED
Communication interface		CAN
Protection		
Over / under voltage protection		Yes
Over current protection		Yes
Over / under temperature protection		Yes
Reverse connection protection		Yes
DC breaker		Yes
General data		
Dimensions (W * H * D)		650 mm * 490 mm * 225 mm
Weight		≤ 55 kg
Degree of protection		IP65
Mounting method		Wall-mounting bracket / Floor-standing bracket
Installation location		Indoor / Outdoor
Operating ambient temperature range		Charge / Discharge: -20 °C to 55°C
Allowable relative humidity range		5% – 95%
Cooling method		Natural convection
Scalability		4 in parallel
Certification		CE, CEC, IEC 62619, IEC 62040, UN 38.3, IEC 63056, IEC 62477

¹⁾ Available in typical conditions

²⁾ EV charger is only available when configured with iHomeManager

³⁾ Available in Q1 2026

⁴⁾ Please refer to the user manual for the full load MPPT voltage range

⁵⁾ The system's charging and discharging capability is also limited by the battery's charging and discharging performance

⁶⁾ Please refer to the user manual and modify the settings based on actual load power

⁷⁾ For micro-inverter compatibility, it is only available for the grid-connection port of the inverter

⁸⁾ Peak charging/discharging power with a duration of 10 s